

BIO-RELO W

Release Oil Winter

BIO-RELO W is used to prevent moist materials from sticking to surfaces at very low temperatures primarily in transportation. The product enables easy unloading even at very low temperatures.

- For trucks (loading bays), steel containers, garbage vessels, excavator scoops etc.
- For transportation of wood chips, food waste, snow/ice, gravel/clay etc.
- The effect can last up to 6 loading cycles depending on loaded material
- Unproblematic in incineration/energy recycling, composting, and digestion to biogas

Use

BIO-RELO W is applied in an even thin layer using a low pressure compressed air sprayer on a surface as clean as possible. Application of the product can be performed down to a temperature of -30°C.

Technical data

Kinematic viscosity

°C	mm ² /s
+ 20	4
0	9
-30	20

Flashpoint	72°C
Biodegradability	>80%*
Biocarbon content	>99%**
VOC	<3%***

Storage

If possible, store the product indoors at a temperature above 0°C.

Environment and Safety

The product is not hazardous to the environment, see safety data sheet (SDS) for more information on handling and safety. Fully REACH-compliant and not classified as dangerous goods.

Packaging

5 liter jerry can, 25 liter jerry can, 208 liter barrel, 1000 liter IBC

CN-number 3403 99 00 00

* After 28 days according to OECD 301 B (readily biodegradable)

** ASTM D6866

*** ISO 11890-2. For comparison diesel has ca. 10% VOC (Volatile organic compounds)