Biobase Sweden AB
Ostmästargränd 8C, SE-120 40 Årsta, SWEDEN
www.bioba.se info@bioba.se +46-(0)8-520 275 90

MADE IN SWEDEN

BIO-FOMO® 2

General purpose form oil

Biobased & Biodegradable

TECHNICAL DATA SHEET

BIO-FOMO®2 is a bio-based form oil of medium viscosity developed to meet future environmental requirements and reduce dependence on fossil resources.

DESCRIPTION

BIO-FOMO®2 is a general-purpose product suitable for most types of concrete work and form materials. Suitable for both vertical and horizontal application. The product is recommended for use down to -5°C. The product is odorless and gives an excellent surface finish without discoloration.

TECHNICAL DATA

Lowest temperature for use	-5 °C
Viscosity at 40°C	13 mm^2/s
Flash point	>100 °C
Biobased carbon content[1]	97 %
German water hazard class	WGK 1
Carbon footprint[2] GWP-GHG	1,69 (kg CO_2-eq/kg)
EPD-IES-0025719:003[3]	
VOC[4]	0 %
Readily Biodegradable[5]	

PRODUCT COMPOSITION

Developed and manufactured by Biobase Sweden AB from renewable raw materials. Bio-based product according to EN 16575:2014.

DIRECTIONS FOR USE

FORM MATERIAL

- ☑ Wood
- ☑ Steel
- ☑ Plastic
- ☐ Polystyrene

The product is applied in a thin, even layer with a low pressure compressed air sprayer or a paint roller. Mop up surplus oil with a rag to avoid pore formation. 1 Liter covers 30–50 m^2

ENVIRONMENT & SAFETY

- REACH-compliant and unclassified according to CLP
- Not classified as dangerous goods
- Safety data sheet available

EPD INTERNATIONAL EPD SYSTEM

Registered in the Swedish BASTA-system with grade ALFA and recommended product at Byggvarubedömningen.

PACKAGING

Our packaging (5, 20, 25, 208,1000 liters) is made of recycled plastic (PE). The product can also be delivered on site through the BASECAMP® filling station.

The product can be stored for up to three years in unopened packaging. Do not store in direct sunlight. Avoid storage at high temperatures.

CN-number 3403 99 00 00



[1]ASTM D6866
[2]Carbon footprint (Cradle-to-Grave) for the liquid (packaging not included) based on third-party verified LCA according to ISO 14040/14044.
[3]EPD International AB: https://www.environdec.com/library/epd25719
[4]Volatile Organic Compounds by weight-%
[5]All components break down to over 60% in 28 days according to OECD 301B.