



**Biobase**<sup>®</sup>

# BIO-FOMO<sup>®</sup> 3

Form Oil

## High Viscosity Form Oil

BIO-FOMO<sup>®</sup> 3 is a bio-based form oil with high viscosity which has been developed for the future to meet the demands on environmental friendliness and independence of fossil resources.

### All products in the FOMO<sup>®</sup>-series are

- Odorless and gives an excellent surface finish without discolorations.
- Fully REACH-compliant and not classified as hazardous according to EU-regulation 1272/2008 (CLP)
- Not classified as dangerous goods
- Bio-based & Biodegradable

BIO-FOMO<sup>®</sup> 3 is especially suitable for porous form materials (wood & plywood) and for vertical application. The product is recommended for temperatures over +5 °C.

#### Use

The product is applied in a thin, even layer with a low pressure compressed air sprayer or a paint roller. Mop up surplus oil with a rag to avoid pore formation. 1 Liter will cover 30-50 m<sup>2</sup>.

#### Tekniska Data

Viscosity at 40 °C	27 mm <sup>2</sup> /s
Flash point	>100 °C
Biocarbon content <sup>1</sup>	99%
PCF <sup>2</sup>	116 g CO <sub>2</sub> /kg
Readily Biodegradable <sup>3</sup>	

<sup>1</sup>ASTM D6866, <sup>2</sup>Product Carbon Footprint (cradle to gate), <sup>3</sup>All components degrades to at least 60% in 28 days in OECD 301B.

#### Storage

Should not be stored in direct sunlight. Can be stored in unbroken containers for up to 3 yrs.

#### Environment & Safety

Approved by the Swedish BASTA-system for worker's safety and environmental concerns, and a recommended product with Byggarubedömningen

(a Swedish construction materials assessment body) See the product safety data sheet for full information on safety and handling.



#### Product Composition

Developed and manufactured by Biobase Sweden AB from renewable raw materials. Bio-based product according to EN 16575:2014.

#### Packaging

5L, 25L, 208L Drum, 1000L IBC

CN-number 3403 99 00 00