



BIO-Multi Multi Purpose Lubricant

Multispray

BIO-Multi is a unique bio-based spray lubricant for various applications that has been developed to meet the demands for the future on environmental friendliness and independence of fossil resources.

Free of fluorinated compounds (PTFE)

- Loosens corroded parts
- Repels moisture and prevents parts from freezing stuck
- Lubricates and reduces friction long term
- Prevents rust/corrosion
- Cleansing and degreasing
- Usable down to -25 °C
- Non-flammable
- Propellant gas is nitrogen (N₂) which does not damage the ozone layer, nor the climate
- Bio-based & biodegradable

Technical Data

| | |
|-------------------------------------|---------------------------|
| Viscosity @ 40 °C | 4 mm ² /s |
| Flashpoint (PM) | 72 °C |
| Biocarbon content ¹ | 99% |
| Carbon Footprint (PCF) ² | 237 g CO ₂ /kg |
| Readily Biodegradable ³ | |

¹ASTM D6866, ²Product Carbon Footprint (cradle to gate, spray can not included), ³All components degrades to at least 60% in 28 days in OECD 301B.

Storage

Pressure vessel must not be exposed to temp. above 50 °C, hot surfaces, sparks, open flames and other sources of ignition. May not be punctured or burned. Applies also to empty container. Protect from sunlight.

Environment and Safety

Fully REACH-compliant and not classified as hazardous according to EU-regulation 1272/2008 (CLP). Does not contain PTFE, nor nanomaterials. See MSDS for further information.

Product Composition

Developed and manufactured by Biobase Sweden AB from renewable raw materials. Bio-based product according to EN 16575:2014.

Packaging

300 ml spray can

CN-number 3403 19 20