

# BIO-FOMO®Eco

*Premium Form Oil*  
*EU Ecolabel*

**Biobased &  
Biodegradable**

## TECHNICAL DATA SHEET

BIO-FOMO®Eco is a bio-based form oil of medium viscosity which has been developed for the future to meet the demands on environmental friendliness and independence of fossil resources.

### DESCRIPTION

BIO-FOMO®Eco is a general-purpose product for most types of concrete work and form materials. The product is recommended for use down to -7°C. The product is odorless and gives an excellent surface finish without discolorations.

### TECHNICAL DATA

Viscosity at 40°C	14 mm <sup>2</sup> /s
Flash point	> 100°C
Biocarbon content <sup>1</sup>	97 %
German water risk class	WGK 1
GISCODE	BTM10
Estimated PCF <sup>2</sup>	170g CO <sub>2</sub> /kg
Readily Biodegradable <sup>3</sup>	

The product can be stored in its original unopened packaging for up to three years. Do not store in direct sunlight or in extreme temperatures.

### PRODUCT COMPOSITION

Developed and manufactured by Biobase Sweden AB from renewable raw materials. Bio-based product according to EN 16575:2014.

<sup>1</sup>ASTM D6866

<sup>2</sup>Product Carbon Footprint (cradle to gate).

<sup>3</sup>All components break down to over 60% in 28 days in OECD 301B.

### DIRECTIONS FOR USE

#### Form Material

- Wood
- Steel
- Plastic
- Styrofoam

The product is applied in a thin, even layer with a low pressure compressed air sprayer or a paint roller. Mop up surplus oil with a rag to avoid pore formation. 1 Liter covers 30-50 m<sup>2</sup>.

### ENVIRONMENT & SAFETY

- REACH-compliant and unclassified according to CLP
- Not classified as dangerous goods
- Bio-based & Biodegradable

The product carries the EU Ecolabel, Licence SE/027/017.



For certified buildings according to DGNB: Indicator 14 quality level 4 (with recognized environmental labeling). See the product safety data sheet for full information on safety and handling.

### PACKAGING

Our packaging is made from recycled plastics (PE).

CN-number 3403 99 00 00

