

Emulsion Form Oil

# BIO-FOMO® E10

*Emulsion based release agent*
**Biobased &  
Biodegradable**

## TECHNICAL DATASHEET

BIO-FOMO® E is a series of bio-based emulsion release agents for concrete casting developed to meet future demands for environmental friendliness in a fossil-free society.

### DESCRIPTION

BIO-FOMO®E10 is a bio-based water emulsion used as a release agent for casting all types of concrete elements. The product is based on vegetable oil and contains components that protect tables and forms from corrosion.

#### Product Properties

- ✓ Good adhesion
- ✓ Self-leveling
- ✓ Easy demoulding
- ✓ Uniform surface color
- ✓ Minimises pores in the concrete surface
- ✓ Storage stable

#### Application Examples

- Wall elements
- Beams and columns
- Balconies
- Floor slabs/half-slabs

### TECHNICAL DATA

Viscosity at 20°C	3.5 mPa s
Lowest usage temperature	0°C
Non-flammable (water based)	
Biocarbon content <sup>1</sup>	78%
VOC <sup>2</sup>	0%
German water risk class	WGK 1
GISCODE	BTM01
Readily biodegradable <sup>3</sup>	

### PRODUCT COMPOSITION

Developed and manufactured by Biobase Sweden AB from renewable raw materials. Bio-based product according to EN 16575:2014.

<sup>1</sup>EN 16640. The oil phase is totally bio-based.

<sup>2</sup>Volatile Organic Compounds weight-%

<sup>3</sup>Degrades 84% in 28 days in OECD 301F

### DIRECTIONS FOR USE

Apply in a thin and even layer with spray equipment that provides fine distribution and good coverage. Wait 15-30 minutes until the white drops have disappeared and a transparent thin layer has formed before pouring begins. Mop or dry the surface before pouring for the best surface finish. Works on most form materials such as steel, form plywood, epoxy and polystyrene. Consumption approx. 1 liter per 50-100 m<sup>2</sup>.

### ENVIRONMENT & SAFETY

Does not contain solvents or biocides, which contributes to a good working environment.

- REACH-compliant and unclassified according to CLP
- Not classified as dangerous goods
- Safety data sheet available

### PACKAGING

Our packaging (20, 208, 1000 liter) is made of recycled plastic (PE).

The product has very good storage stability, at least 9 months from the date of manufacture.

The product should be stored at 0 to +35 °C. Do not store in direct sunlight.



CN-number 3403 99 00 00

